





This is to certify that: ISEO Serrature SpA

Via San Girolamo, 13

Pisoane **Brescia** 25055 Italy

Holds Certificate Number: 0086 CPR 747913

In respect of:

BS EN 1125:2008 - Mod. IDEA BASE Panic Exit Devices. Mechanically operated by either a horizontal push-bar or a horizontal touch-bar, specifically designed for use in a panic situation on escape routes.

In compliance with the Regulation (UK) Statutory Instrument 2019 No 465 of the United Kingdom Parliament (Construction Products (Amendment etc.) (EU Exit) Regulations or CPR), this certificate applies to the above construction product. This certificate attests that all the provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the above standard(s) under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product. This certificate was first issued on the date below and will remain valid as long as neither the designated standard, the construction product, the AVCP methods, nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the approved product certification body.

For and on behalf of BSI, an Approved Body for the above Regulation (Approved Body Number 0086):

Frank Lee, Product Certification Technical and Compliance Director

First Issued: 2021-07-16 Latest Issue: 2021-07-16

Effective Date: 2021-07-16

Page: 1 of 5

...making excellence a habit.™

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.

To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated online.

No. 0086 CPR 747913

BS EN 1125:2008 - Building hardware - Panic exit devices operated by a horizontal bar, for use on escape routes.

<u>Table 1</u> : Requirements for panic exit devices in line with BS EN 1125:2008 (to be read in conjunction with Tables 2 & 3)					
Product:	Panic exit devices operated by a horizontal bar as covered by the scope of BS EN 1125:2008.				
Intended use:	For doors on escape routes.				
Essential characteristics	Clauses within	Compliance			
Lasentiai Ciiai actel IstiCs	EN 1125:2008	Mod. IDEA BASE			
Ability to release (for doors on escape routes)	4.2.1	Pass			
Durability of ability to release against aging and degradation (for doors on escape routes)	4.2.1	Pass			
Self closing ability C (for fire/smoke doors on escape routes)	4.2.1	Pass			
Durability of self closing ability C against aging and degradation (for fire/smoke doors on escape routes)	4.2.1	Pass			
Resistance to fire E (integrity) and I (insulation) (for fire doors on escape routes	4.2.1	Pass			
Control of Dangerous substances	4.1.25	Pass			
Note:	This details only those essential characteristics as required in the ZA Annex of BS EN 1125:2008 and applicable to a horizontal bar operation.				

First Issued: 2021-07-16 Effective Date: 2021-07-16

Latest Issue: 2021-07-16

Page: 2 of 5

No. 0086 CPR 747913

BS EN 1125:2008 - Building hardware - Panic exit devices operated by a horizontal bar, for use on escape routes.

<u>Table 2</u> : Product Information – Panic Exit Devices suitable for use on smoke door
assemblies – based on the requirements of BS EN 179:2008 Annex B.1

	T	T	T
No	Description	Additional Information	Model
1	Panic exit device	Panic exit device operated by a horizontal bar	Mod. IDEA BASE
Mode	dels 946*****5*		
Acces	94100***, 9409****, 94021***, 85900085*, 5680***, 94100***, 941***35**, 941020***5, 00E1*2****+567E0000540 (ARIES), 00E1*4****+567E0000540 (ARIES)		
Note		Panic exit devices detailed in table 2 have conformed to the requirements of BS EN 1125:2008, Table 1: Performance characteristics and compliance criteria.	

First Issued: 2021-07-16 Effective Date: 2021-07-16

Latest Issue: 2021-07-16

Page: 3 of 5

No. 0086 CPR 747913

BS EN 1125:2008 - Building hardware - Panic exit devices operated by a horizontal bar, for use on escape routes.

<u>Table 3</u> : Product Information – Panic Exit Devices suitable for use on fire and smoke door
assemblies

No	Description	Additional Information	Model
2	Panic exit device	Panic exit device operated by a horizontal bar	Mod. IDEA BASE
Mod	IDEA PAD 946*****5*, IDEA-PAD BOLT 947*****4*		***4*
9430020*, 9430030*, 94000030, 94100**		941000****, 9410201**4, 9410203**4, 9410204 9430020*, 9430030*, 94000030, 94100***, 9410 9401****1, 00E1*2****+567E0000540 (ARIES) 00E1*4****+567E0000540 (ARIES)	003*04, 941020***4,
Note Panic exit devices detailed in table 2 have conformed to the requ BS EN 1125:2008, Table 1: Performance characteristics and com criteria.			

First Issued: 2021-07-16 Effective Date: 2021-07-16

Latest Issue: 2021-07-16

Page: 4 of 5

No. 0086 CPR 747913

Manufacturing Plant

Certified Activities

E01

BS EN 1125:2008 – Building hardware – Panic exit devices operated by horizontal bar, for use on escape routes.



First Issued: 2021-07-16 Effective Date: 2021-07-16

Latest Issue: 2021-07-16

Page: 5 of 5