Evidence of Performance

Joint sound reduction of seals

Test Report 24-002443-PR01

(PB 01-K06-04-en-01)

Client C.C.E. srl

Costruzioni Chiusure Ermetiche Via dell'Artigianato 16 35010 Villa del Conte (PD)

Automatic drop down seal, single-side activation

Designation

Alu Plus

Cross section of sealing groove

17 mm × 18 mm

Seal type

Air gap w 7 mm

Special features

Weighted sound reduction index of joints R_{S.w} Spectrum adaptation terms C and Ctr



Floor seal type I with air gap $w = 7 \text{ mm } (n^{\circ}T02)$

 $R_{S,w}(C; C_{tr}) = 48 (-1; 1) dB$

ift Rosenheim 08.10.2024

Dr. Joachim Hessinger, Dipl.-Phys. Head of Testing Department

Building Acoustics

Johann Baume, Dipl.-Ing. (FH) **Operating Testing Officer Building Acoustics**



Basis

EN ISO 10140-1: 2021 EN ISO 10140-2: 2021 EN ISO 717-1: 2020

Representation



Instructions for use

This procedure is suitable for the comparison of construction products designed for sealing (e.g. gaskets/seals, fillers for joints). The results can be used to evaluate the sound power ratio τ_e according to EN ISO 12354-3 Annex B. Using the calculated sound reduction of the joint for the calculation of the overall sound reduction is not a substitute for the sound reduction verification of the overall construction. For Germany the following applies:

The weighted joint sound reduction index R_{s,w} can be used for the prognosis of the sound insulation of doors according to DIN 4109-35: 2016.

Validity

The data and results given relate solely to the tested and described specimen.

Testing the sound insulation does not allow any statement to be made on any further characteristics of the present construction regarding performance and quality.

Notes on publication

The ift Guidance Sheet "Conditions and Guidance for the Use of ift Test Documents" applies.

The cover sheet can be used as abstract.

Contents

The test report contains a total of 10 pages.

- Object
- Procedure
- Detailed results
- 4 Instructions for use







