

# Product data sheet

## TS 5000

Overhead door closer with guide rail for single-leaf doors with a leaf width up to 1400 mm



### Product features

Closing force of EN2-6 with variable adjustment
Can be used for right and left hand doors without conversion
Hydraulic latching action which accelerates the door shortly before the closed position
Closing speed can be individually adjusted
Integrated back check, slows down doors that are thrown open forcefully
Visual closing force display for easy control of the setting
All functions can be adjusted from the front

### Application Areas

Fire and smoke protection doors
Right and left single-action doors
Single-action doors up to 1400 mm leaf width
Door leaf installation hinge side and transom installation opposite hinge side

### Product Data Table

Productname	TS 5000
Closing force in accordance with EN 1154	EN 2 - 6
Barrier-free in accordance with DIN 18040 up to leaf width (max.) in mm	1100 mm
Leaf width (max.)	1400 mm
DIN direction	Door leaf installation hinge side, Transom installation opposite hinge side
Door opening angle (max.)*	180 °
Suitability for fire protection doors	Yes
Closing force adjustable	Yes, stepless
Adjustable closing speed	Yes
Latching action adjustable	Yes, via valve
Back check integrated	Yes, hydraulically adjustable
Position of closing force adjustment	Front
Visual closing force display	Yes
Hold-open device	Optional

### Accessory

Product name
Mechanical hold-open unit
Flexible opening restrictor
Cover cap door closer

### Part

Product name
Guide rail TS 3/5000 vertically adjustable
Guide rail TS 3/TS 5000
TS 5000 door closer
T-Stop guide rail TS 3/5000